

DOCKET NO. : ADCM-0003

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Application of:
LESTER L. JARRELL

Serial No.: HEREWITH

Group Art Unit: Unknown

Filing Date: HEREWITH

Examiner: Not yet assigned

For: TELEVISION AUDIENCE MONITORING SYSTEM AND METHOD
EMPLOYING DISPLAY OF CABLE CONVERTER BOX

EXPRESS MAIL LABEL NO: EM155911260US

DATE OF DEPOSIT: October 9, 1998

Box ☒ Patent Application
☐ Provisional ☐ Design ☐ Sequence

Assistant Commissioner for Patents
Washington DC 20231

Sir:

PATENT APPLICATION TRANSMITTAL LETTER

Transmitted herewith for filing, please find

☒ A Utility Patent Application under 37 C.F.R. 1.53(b).

It is a continuing application, as follows:

☐ continuation ☐ divisional ☐ continuation-in-part of prior application number
____/____.

☐ A Provisional Patent Application under 37 C.F.R. 1.53(c).

☐ A Design Patent Application (submitted in duplicate).

Including the following:

☐ Provisional Application Cover Sheet.

☒ New or Revised Specification, including pages 1 to 21 containing:

☒ Specification

☒ Claims

☒ Abstract

☐ Substitute Specification, including Claims and Abstract.

☐ The present application is a continuation application of Application No. _____ filed _____. The present application includes the Specification of the parent application which has been revised in accordance with the amendments filed in the parent application. Since none of those amendments incorporate new matter into the parent application, the present revised Specification also does not include new matter.

☐ The present application is a continuation application of Application No. _____ filed _____, which in turn is a continuation-in-part of Application No. _____ filed _____. The present application includes the Specification of the parent application which has been revised in accordance with the amendments filed in the parent application. Although the amendments in the parent C-I-P application may have incorporated new matter, since those are the only revisions included in the present application, the present application includes no new matter in relation to the parent application.

☐ A copy of earlier application Serial No. _____ Filed _____ to which no new matter has been added TOGETHER WITH a copy of the executed oath or declaration for such earlier application and all drawings and appendices. Such earlier application is hereby incorporated into the present application by reference.

☐ Please enter the following amendment to the Specification under the Cross-Reference to Related Applications section (or create such a section) : "This Application is a

☐ continuation or ☐ divisional of Application Serial No. _____
_filed _____

_____."

- ☐ Signed Statement attached deleting inventor(s) named in the prior application.
- ☐ A Preliminary Amendment.
- ☒ 4 Sheets of ☐ Formal ☒ Informal Drawings.
- ☐ Petition to Accept Photographic Drawings.
- ☐ Petition Fee
- ☒ An ☒ Executed ☐ Unexecuted Declaration or Oath and Power of Attorney.
- ☒ An Associate Power of Attorney.
- ☒ An ☒ Executed ☐ Copy of Executed Assignment of the Invention to ADCOM Information Services, Inc.
- ☒ A Recordation Form Cover Sheet.
- ☒ Recordation Fee - \$40.00.
- ☐ The prior application is assigned of record to _____
- ☐ Priority is claimed under 35 U.S.C. § 119 of Patent Application No. _____ filed _____
in _____ (country).
- ☐ A Certified Copy of each of the above applications for which priority is claimed:
- ☐ is enclosed.
- ☐ has been filed in prior application Serial No. _____ filed _____
- ☐ An ☐ Executed ☐ Unexecuted ☐ Copy of Earlier Statement Claiming Small Entity Status under 37 C.F.R. 1.9 and 1.27
- ☐ is enclosed.
- ☐ has been filed in prior application Serial No. _____ filed _____
said status is still proper and desired in present case.
- ☐ Diskette Containing DNA/Amino Acid Sequence Information.

- ☐ Statement to Support Submission of DNA/Amino Acid Sequence Information.
- ☐ The computer readable form in this application _____, is identical with that filed in Application Serial Number _____, filed _____. In accordance with 37 CFR 1.821(e), please use the ☐ first-filed, ☐ last-filed or ☐ only computer readable form filed in that application as the computer readable form for the instant application. It is understood that the Patent and Trademark Office will make the necessary change in application number and filing date for the computer readable form that will be used for the instant application. A paper copy of the Sequence Listing is ☐ included in the originally-filed specification of the instant application, ☐ included in a separately filed preliminary amendment for incorporation into the specification.
- ☐ Information Disclosure Statement.
- ☐ Attached Form 1449.
- ☐ Copies of each of the references listed on the attached Form PTO-1449 are enclosed herewith.
- ☐ A copy of Petition for Extension of Time as filed in the prior case.
- ☐ Appended Material as follows: _____
- ☒ Return Receipt Postcard (should be specifically itemized).
- ☐ Other as follows: _____

FEE CALCULATION:

- ☐ Cancel in this application original claims _____ of the prior application before calculating the filing fee. (At least one original independent claim must be retained for filing purposes.)


			SMALL ENTITY		NOT SMALL ENTITY	
			RATE	FEE	RATE	FEE
PROVISIONAL APPLICATION			\$75.00	\$	\$150.00	\$
DESIGN APPLICATION			\$165.00	\$	\$330.00	\$
UTILITY APPLICATIONS BASE FEE			\$395.00	\$	\$790.00	\$790.00
UTILITY APPLICATION; ALL CLAIMS CALCULATED AFTER ENTRY OF ALL AMENDMENTS						
	No. Filed	No. Extra				
TOTAL CLAIMS	20 - 20 =	0	\$11 each	\$	\$22 each	\$0
INDEP. CLAIMS	3 - 3 =	0	\$41 each	\$	\$82 each	\$0
FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM			\$135	\$	\$270	\$
ADDITIONAL FILING FEE				\$		\$
TOTAL FILING FEE DUE				\$		\$790.00

- ☒ A Check is enclosed in the amount of \$ 790.00.
- ☒ The Commissioner is authorized to charge payment of the following fees and to refund any overpayment associated with this communication or during the pendency of this application to deposit account 23-3050. This sheet is provided in duplicate.
- ☐ The foregoing amount due.
- ☒ Any additional filing fees required, including fees for the presentation of extra claims under 37 C.F.R. 1.16.
- ☒ Any additional patent application processing fees under 37 C.F.R. 1.17 or 1.20(d).
- ☐ The issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance.
- ☒ The Commissioner is hereby requested to grant an extension of time for the

appropriate length of time, should one be necessary, in connection with this filing or any future filing submitted to the U.S. Patent and Trademark Office in the above-identified application during the pendency of this application. The Commissioner is further authorized to charge any fees related to any such extension of time to deposit account 23-3050. This sheet is provided in duplicate.

SHOULD ANY DEFICIENCIES APPEAR with respect to this application, including deficiencies in payment of fees, missing parts of the application or otherwise, the United States Patent and Trademark Office is respectfully requested to promptly notify the undersigned.

Date: October 9, 1998



Lawrence A. Aaronson
Registration No. 38,369

Woodcock Washburn Kurtz
Mackiewicz & Norris LLP
One Liberty Place - 46th Floor
Philadelphia PA 19103
Telephone: (215) 568-3100
Facsimile: (215) 568-3439

© 1997 WWKMN

TELEVISION AUDIENCE MONITORING SYSTEM AND METHOD EMPLOYING DISPLAY OF CABLE CONVERTER BOX

FIELD OF THE INVENTION

The present invention relates to a device for monitoring usage of audiovisual
5 equipment. In particular, the present invention relates to a device for interfacing with set-top
converter boxes to determine a channel being watched by a television viewer.

BACKGROUND OF THE INVENTION

Determining a number of viewers watching a particular television program is
of great importance to television networks, stations, programmers and advertisers.
10 Information regarding the number of viewers is used to determine market share and the ratings
of particular programs. This information is additionally used to determine advertising rates,
which in turn affects the revenue generated by the television networks and stations.

There are numerous systems known in the art that attempt to monitor the
viewing habit of television watchers. Early attempts at monitoring were fairly simple and
15 unsophisticated, and generally required viewers to maintain a diary of programs watched. As
the viewers began and finished watching a particular channel or program, they entered a start
and end time in to the diary. The viewers periodically mailed the diaries to a central collection
location, which then processed the diaries. The disadvantages of such a system are many,
including: failure to enter information into the diaries, inaccurate entries into the diaries, and

delays in processing. Further, as the number of channels provided to households has increased dramatically, it has become increasingly difficult for viewers to accurately track their viewing habits.

Later attempts have become more sophisticated and efficient by automating portions of the data collection process and the determination of the channel currently being viewed. For example, U.S. Patent No. 4,642,685, to Roberts et al., discloses a television monitoring system having a channel detection unit, a people monitoring unit, a transmission unit, and a receiving unit. The channel detection unit detects ultra or very high frequency radiation emitted from a television tuner to determine if the channel being tuned is one of the channels which have been preset into the detection unit. The detection is performed by a pick-up probe that inductively couples the signal emitted from the local oscillator of the television receiver. The people monitor unit is a powered handset that includes buttons assigned to each of the individuals who will be viewing the television set. The viewer depresses his or her assigned button to indicate he or she has started to watch the television. The viewing data is stored and transmitted by the transmission unit over household wiring to the receiving unit. The receiving unit sends the collected information to a central computer via a telephone connection. While this system speeds the data transmission process to the central computer as compared to mailing diaries to a processing center, there are several disadvantages in this system. For example, those of skill in the art will recognize that the location of the pick-up probe will greatly affect the sensitivity and accuracy of the channel detection unit. Further, as each viewer must manually depress a button on the people monitor, it is subject to the same inaccuracies of the diary method noted above, i.e., the failure of viewers to record the television channels actually watched.

U.S. Patent No. 4,907,079, to Tuner et al., describes networked conventional audio and visual equipment that communicate via telephone lines with a remote central computer. The viewer provides channel selection commands or other programming commands to a microprocessor through an infrared remote control. A VCR tuner and TV tuner within the system provide audio and video signals for the conventional television monitor or television receiver. An AM and FM radio tuner may also be included, tunable by the microprocessor. In the Tuner et al. system, the video and/or audio signals from each tuner,

video tape player, and disc players are coupled to the input side of an audio switch and a video switch. The switches are microprocessor controlled so that the audio and video program from any source may be coupled to any output or display device at the viewing location. The system includes a motion detector to determine the presence of viewers and provides for
5 communication with a remote computer to monitor use of each networked audiovisual unit. While this system provides for monitoring and logging of each networked audiovisual unit, the Tuner et al. system is designed to control a large home-entertainment system, rather than a small-scale solution to monitoring viewers' habits. In particular, the Turner et al. system is indicated to cost a few hundred dollars, and would fail to provide a solution to television
10 networks and advertisers who are interested in obtaining accurate viewing statistics by deploying systems to a relatively large number of viewers.

U.S. Patent No. 4,912,552, to Allison, III, et al., describes a system that collects television channel tuning data that transmits the data to a central site in a transparent manner to the occupants of the household. The system is designed having a hub and spoke
15 architecture, where the hub unit communicates with metering devices attached to television receivers and/or cable television converters. The meters are periodically polled by the hub, which then collects the data acquired by each meter. The hub communicates with a host computer via standard telephone lines. The Allison, III, et al. system particularly describes the central hub device and gathering data before transmitting it to the central site. However,
20 the Allison, III et al. system fails to provide an improved metering unit by contemplating the use of known channel meters.

U.S. Patent No. 5,374,951, to Welsh, discloses a system for monitoring and recording data related to television program viewing habits that includes a plurality of remote program monitor units that automatically report such data to a central computer via a
25 conventional telephone network. The monitor unit reads a character string that is decoded from the demodulated television signal received by the unit. The character string is compared to a string table stored within the unit to determine the content being viewed by the television watcher. If there is a match, an event code and a time are stored in the unit for reporting to the central computer. However, for the system to operate, the character string must be
30 encoded into the received television signal, otherwise there will be no match with the string

table stored in memory. Further, the string table must be kept current for the system to provide accurate results.

U.S. Patent No. 5,382,970, to Kiefl, describes a system for monitoring and collecting data on the viewing habits of television viewers that includes a portable personal data collection device that is separate from the television or set-top converter. The personal data collection devices includes a detector for providing a station identifier identifying the particular broadcast signal being received by the receiver, a clock for providing a signal representing time, a memory for storing data, and a cellular telephone module for communicating with a central location. The cellular telephone module periodically transmits stored data within the device to the central location. The viewer may enter channel information directly into the device, or the device may include a detector for detecting a channel selection signal from a television remote control to change the station identifier stored in memory. While this is an improvement over diaries, this system requires a personal data collection device for each individual watching a particular television set. Further, because the device is physically separate from the television set, the data collected may not be accurate as viewers may either fail to enter channel information or the device may not detect an infrared transmission from the television remote control.

U.S. Patent No. 5,495,282, to Mostafa, et al., discloses a tuning/monitoring module for monitoring use of a video equipment without the use of probes by injecting RF signals into a cable converter and a VCR in order to detect channels selected by the cable converter and the VCR. In accordance with signals received from the cable converter and the VCR, the tuning/monitoring module can determine a selected channel being viewed by the viewers. Channel identification signals are also injected into the VCR and cable converter for recording by the VCR on videotape. The state of the "TV/VCR" switch of the VCR is determined by injecting a code signal into the VCR and determining whether that signal is present in an RF video signal output by the VCR. The receiver also receives data contained in channel identification signals. The receiver is selectively connectable to the VCR and the cable converter. However, this system requires the use of the special tuning/monitoring module in place of a tuner provided with a television or VCR in order to provided the injected

signal to determine the viewed channel. Such a special tuning/monitoring module increases the expense associated with tracking viewers' habits.

In view of the above, there is a need for an integrated solution to detect the channels being watched by viewers. There is also a need for a system that does not interfere with any of the consumer's electronics, equipment or features. In particular, there is a need for a system that provides channel information without requiring addition steps to be taken by viewers, and that functions such that the consumer's VCR, TV, remote controls are not tampered with or opened and continue to operate normally.

SUMMARY OF THE INVENTION

In view of the above, the present invention, through one or more of its various aspects and/or embodiments is thus presented to accomplish one or more objects and advantages, such as those noted below.

According to an aspect of the present invention, there is provided a display interface device for use in determining a currently tuned-to channel of a set-top converter box having an electronic display, where the electronic display indicates the currently tuned-to channel in response to drive signals provided thereto by the set-top converter device. The display interface device comprises an electrical connection to the electronic display and a controller that is connected to the electronic display by the electrical connection. The controller receives the drive signals transmitted to the electronic display by the set-top converter device and interprets the drive signals to generate information representative of the currently tuned-to channel.

According to a feature of the present invention, the electronic display comprises at least one seven-segment display element, and the seven-segment display element is adapted to display an alphanumeric character representation of the currently tuned-to channel of the set-top converter box. The drive signals are provided to plural seven-segment display elements in the electronic display using a multiplexing scheme in order to display each alphanumeric character of the currently tuned-to channel. Further, the drive signals may comprise scan signals provided over scan lines that selectively enable one seven-segment display element in the electronic display and segment signals provided over segment lines that

drive each segment of the seven-segment display element. The scan lines and the segments lines are input to predetermined pins of an input/output port of the controller in order to determine the currently tuned-to channel.

According to another feature, the information representative of the tuned
5 channel may be output to a second device connected to the display interface via a second electrical connection. The second device may stores receive and further process the information representative of the currently tuned-to channel. In addition, the display interface board may be adapted to receive power and additional data via the second electrical connection.

10 According to yet another feature, the second device may comprise a viewership collection meter and the information representative of the tuned channel may be coded as an ASCII value representative of the currently tuned-to channel and output to a viewership meter connected to the display interface via a second electrical connection. The viewership meter may also include an audio matching circuit that compares a first audio signal of a
15 predetermined channel tuned by the viewership collection meter with a second audio signal output by a television to which the set-top converter is connected, wherein if the first audio signal and the second audio signal match, the viewership collection meter determines that the channel to which the set-top converter box is tuned is the predetermined channel.

According to another aspect of the present invention, there is provided a system
20 for determining viewership of channels tunable by a set-top converter box having an electronic display. The system comprises a display interface device connected to the electronic display, and a viewership collection meter connected to the display interface that periodically stores a channel to which the set-top converter is tuned. The channel to which the set-top converter is tuned is determined by the display interface and communicated to the
25 viewership collection meter, and the viewership collection meter stores the channel and forwards it to a predetermined location at selected times.

According to yet another aspect of the present invention, there is provided a method of determining a channel to which a set-top converter box is tuned using a display interface where the set-top converter comprises an electronic display that is driven by drive
30 signals. The method comprises receiving drive signals at the display interface; determining

a channel to which the set-top converter box is tuned by sampling the drive signals; generating a coded representation of the determined channel; and outputting the coded representation.

According to a feature of the method, the electronic display comprises at least one seven-segment display element, and the drive signals comprise scan signals provided over
5 scan lines that enable each seven-segment display element and segment signals provided over segment lines that drive each segment of the seven-segment display element. The step of determining a channel to which the set-top converter box is tuned further comprises (a) determining if a scan line for the seven-segment display element is active; (b) if the scan line is active at step (a), then determining which of the segment lines are active to determine
10 character being displayed by the seven-segment display element; and (c) repeating steps (a) and (b) for each seven-segment display element in the electronic display.

According to another feature of the method the step of generating a coded representation of the determined channel comprises generating an ASCII value of the channel to which the set-top converter box is tuned. Outputting the coded representation may
15 comprise serially transmitting the ASCII value to a viewership meter. The ASCII value may be stored at the viewership meter and forwarded at predetermined times to a central collection site.

Other features of the invention are described below.

BRIEF DESCRIPTION OF THE DRAWINGS

20 The foregoing summary, as well as the following detailed description of the preferred embodiments, is better understood when read in conjunction with the appended drawings. For the purpose of illustrating the invention, there is shown in the drawings an embodiment that is presently preferred, in which like references numerals represent similar parts throughout the several views of the drawings, it being understood, however, that the
25 invention is not limited to the specific methods and instrumentalities disclosed. In the drawings:

Figure 1 is an overview of the environment in which the television audience monitoring system of the present invention may be implemented;

Figure 2 is a block diagram illustrating the interconnection of a television signal converter box and display interface circuit;

Figure 3 is a schematic diagram illustrating a plurality of light emitting diodes display of the television signal converter box and the display interface circuit;

5 Figure 4 is a block diagram of an exemplary collection meter in accordance with an aspect of the present invention; and

Figure 5 is an exemplary flow chart illustrating the steps and processes performed by a microcontroller included with the display interface circuit.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

10 The present invention provides a method and apparatus for detecting the currently tuned-to channel of a subscriber's set-top converter box having an electronic display that indicates the channel and status. The information related to the detected channel may then be forwarded to a data collection system within the subscriber's home or other location for eventual transmission to a central data collection and compilation site. Such information,
15 taken from a large sample size, may be used to measure network viewing and the interactive environment.

In order to obtain accurate viewership data, it is preferable to gather data from a large sample of subscriber homes within a cable satellite system's broadcast base. The sample is typically derived from demographic and lifestyle characteristics, shopping patterns,
20 and consumer profile of the subscribers' homes. Ideally, the sample of homes from the entire system should represent the system as a whole. To collect data, each of the homes to be sampled may be supplied with a viewership meter (described below). The viewership meter is preferably supplied by ADcom Information Services, Inc., Carlsbad, California, and is installed on each television in the sampled homes. Such a meter is quickly and easily installed
25 as compared to other known meters and provides a complete record of viewing in each participating household. When the quantitative ratings from the viewership meters are compiled, the information may be used by advertisers and network programmers to accurately target audiences and determine ideal spot placement for advertisements.

Referring to Figure 1, there is illustrated an overview of an exemplary environment within which the present invention may be embodied. As illustrated, signals from a satellite/cable system provider are received via transmission lines 11 connected to one of a satellite dish 13 or power poles 15. The satellite dish 13 may receive signals from a plurality of earth orbiting satellites (not shown), whereas the transmission lines 11 strung over power poles 15 (or buried underground) may be connected to a transmission site (not shown). The transmission lines 11 enter the viewer's home or other location and are typically connected to a wall plate 12 having a 75Ω co-axial connector.

To provide a signal to a viewer's television set 10, a first 75Ω co-axial cable 14 electrically connects the transmission line 11, at the wall plate 12, to a first connection on, e.g., the rear panel of a set-top converter box 16. A second 75Ω co-axial cable 14 connects between a second connection on the rear panel of the set-top converter 16 and to, e.g., a 75Ω connector in a television set 10. The set-top converter box 16 is used to selectively tune channels in accordance with a viewer selection. Alternatively, a single 75Ω co-axial cable 14 may be used to provide signals directly to the television set 10. Also as shown, the television set includes an audio-out jack 10a.

The set-top converter 16 is connected to a viewership collection meter 18 by wires or a cable 24. Alternatively, an electrical connector or the like may be used in place of wires or cabling 24 to connect the viewership meter 18 and the set-top converter 16. The viewership meter 18 is designed such that it may connect to any television 10 or set-top converter 16. In accordance with an aspect of the present invention, the collection meter 18 determines a viewed channel by receiving channel-related information from a display interface board 22 (described below with regard to Figures 2 and 3). The collection meter 18 may also use an audio matching technique to log channel viewership throughout the day. The collection meter 18 is preferably capable of recording the channel location (i.e., the tuned channel) every five seconds, storing the information and forwarding it to a central computer (not shown). The data is forwarded by telephone or other means during time periods when the transmission to the central site is unlikely to interfere with the occupants' use of the transmission media. The central computer collects the data from all viewership meters 18, analyzes the information, combines the records with additional qualitative data, and sends

prepared reports to the system operator as early as the next day. Preferably, hundreds, or even thousands of viewership meters 18 may be managed from one central system. Data and reports are received by the system operators via e.g., the Internet and Frame Relay routers. System personnel can quickly generate custom reports that show channel ratings by day, target
5 and network ranking.

Referring now to Figures 2 and 3, there is illustrated a display interface board 22 of the present invention. The display interface board 22 is preferably provided within the collection meter 18 and includes a microcontroller U6, a connector J2, and a capacitor C1, which is charged from a voltage source Vcc. The microcontroller U6 is preferably an 8-bit
10 microcontroller having a Reduced Instruction Set Computer (RISC) architecture and includes dedicated digital input lines, digital output lines and an on-board programmable memory. The microcontroller U6 receives channel data from the set-top converter box 16, stores the data in an internal random access memory (RAM) or other memory, and converts the data into an ASCII channel value that is serially transmitted to the components within collection meter 18
15 over line 20. Other data formats compatible with the collection meter 18 may be used. The microcontroller U6 may also provide capabilities such as a real-time clock, a modem chip-set. Preferably, the microcontroller U6 comprises a AT90S1200, manufactured by Atmel Corporation, San Jose, California. Other similar microcontrollers may be used, as the present invention is not limited to the above-noted microcontroller.

As illustrated the interface board 22 is connected by wires 24 or other means
20 to each of one or more seven-segment light emitting diode (LED) display elements 23a-c of the set-top converter box 16. It is preferable that the LED display elements 23 are driven in a multiplexed fashion and have a common cathode or common anode design. It is noted that segments in LED displays 23 having the multiplexed driving scheme are scanned and driven
25 one at a time at a scan rate of a few hundred Hertz. Further, although three LED displays 23a-c are illustrated in the Figures, it is within the scope of the present invention to include fewer or more LED displays 23 or other displays capable of displaying alphanumeric information. One end of the wires 24 is connect to respective leads from jumper P2, which supplies drive signals to the LEDs of the display elements 23. The other end of the wires 24 are connected
30 to appropriate port pins of the input/output (I/O) ports of the microcontroller U6. At

predetermined times, the port pins are sampled, and based on the voltages present at the pins, the microcontroller U6 determines and outputs the ASCII representation of the channel value over the I/O port, which is connected to connector J2. Additionally, other data and power may be transferred between the display interface board 22 and external devices over connector J2.

- 5 It is noted that additional or fewer connectors may be provided on the display interface 22. For example, a single connector may be provided to provide all of the above-noted features at a reduced cost.

Figure 4 is a block diagram of the exemplary components within the collection meter 18. The collection meter 18 generates "snapshots" of selected channels on cable,
10 satellite and standard air systems and compiles information related to the snapshots. The information may include the channel or channels viewed at a particular time or on a particular day. The compiled information may be used to generate viewership ratings and other research related services for multi-channel subscriber television systems (e.g., cable television and satellite television).

- 15 The collection meter 18 includes Audio interface circuits 32, a communications module 26, a digital signal processor (DSP) controller 27, a flash memory 28 to store parameters and programming information for the DSP controller 27, a CODEC 30 to provide for compression and decompression of data (e.g., audio or video information) in accordance with predetermined mathematical algorithms, a real time clock 30, and a power supply and
20 voltage supervisor 31. The DSP controller 27 may be programmed to provide functionalities such as, tuning to cable channel frequencies, detection of the state of the television (e.g., powered ON or OFF), detection of the channel being viewed, communication to the communications module 26, management of storage of snapshot information (e.g., time stamp), reception and storage of information related to a telephone number of a central
25 collection site and time for sending snapshot information to the central site, dial-up capability to contact the central site and to upload the snapshot information, and a capability to receive time and reset the onboard real time clock during the upload. Additional features and functionalities may be provided as user requirements change by reprogramming the DSP controller 27. As illustrated, the DSP controller 27 receives information over line 20 from the
30 display interface board 22 (from connection J2).

The dial-up capability is preferably programmed in firmware within the DSP controller 27 and is preferably not programmable by end-users (e.g., viewers). To performed the dial-up function, the communications module 27, which is connected to the customer's telephone line, is taken off-hook in accordance with the V.22 protocol at predetermined times and dual-tone multi-frequency (DTMF) signals are transmitted to call the central collection site. The telephone number of the central collection site is preferably coded into the firmware and may be changed by the central site during data communications. Using the V.22 protocol, the communications module 27 transmits signals representative of the data collected by the collection meter 18 to the central site. As illustrated in Figure 4, the communications module 27 may comprise a MODEM.

The power supply 31 regulates the voltage to the communications module 27 and the Audio interface circuits 32. The power supply 31 receives, for example, 12VAC and may provide, $\pm 5V$ and $\pm 12V$ DC to the modules 27 and 32. The voltage supervisor portion monitors the $+5V$ and $+12V$ and resets the DSP controller 26 and the flash memory 28 if the supplied voltage drops below these values. The total power consumption is preferably less than 5 Watts.

The Audio interface circuits 32 include an RF amplifier 33, a mixer 34, an FM demodulator 35, a low-pass filter 36, audio comparator 37, voltage controlled oscillator (VCO) 38, and a frequency synthesizer 39. The broad-band cable signal to the television set 10 enters through a coaxial cable 14 coupled to the Audio interface circuits 32. The audio sub-carrier of a particular cable channel is coupled to the low pass filter 36 and the RF amplifier 33 by a low-loss coupler. The signal is converted to a predetermined frequency (e.g., 3.25 MHz) by the mixer 34, the local oscillator 38 and the frequency synthesizer 39, which is controlled by the DSP controller 27. The predetermined frequency is demodulated by the FM demodulator 35 so the audio program for a tuned channel may be recovered. The audio signal from the television set 10 is obtained from an audio pick-up device (not shown) or from the audio jack 10a in the television set 10. The audio pick-up device is coupled to the television set 10 to detect the audio signal broadcast. The audio signal is fed to the RF amplifier 33 and then into an audio comparator 37. The recovered audio from the FM demodulator 35 is also fed into the audio comparator 37 and compared with the television

audio signal. If the audio frequencies match, then a logic high signal is sent by the audio comparator 37 to the DSP controller 27. If there is not a match between the recovered audio from the FM demodulator 35 and the television audio, then the DSP controller 27 tunes the frequency synthesizer 39 to the next channel and continues until a match is found.

5 The collection meter 18 may be enclosed in an assembly (not shown) that includes internal-metalized plastic covers. The Audio interface circuits 32 may be mounted on the bottom cover and the communication module 27 mounted up-side-down on the top of the Audio interface circuits 32. The display interface circuits 22 may be mounted on the top cover. The assembly may include the following interfaces: a 75Ω cable in (54 MHz to 1
10 GHz, -16dBmV to +10 dBmV), a power adapter in (12 VAC, <420mA), audio in ($1V_{p-p}$, 100 Hz to 5kHz, $>1k\Omega$ impedance), a magnetic sensor in ($5mV_{p-p}$, 100 Hz to 5 kHz, $1k\Omega$ impedance), a POTS In/Out (RJ-11, meets FCC Part 68 requirements), and a power/mode indicator (green LED).

 The various components and specifications noted-above with regard to the
15 collection meter 18 have been provided herein for exemplary purposes only. Other components and different specifications are intended to be within the scope of the present invention. For example, the collection meter 18 may include a microprocessor or microcontroller and associated circuitry to perform the various functions of the DSP controller 27. Further, additional or fewer communications interfaces may be provided (e.g., power line
20 data communication, RF data communication, or digital telephony).

 Figure 5 is a exemplary flowchart of the sequence of operations performed by the microcontroller U6 in accordance with an aspect of the invention. At step 100 the variables, data space and serial ports are initialized. At step 102, the microcontroller I/O ports are initialized and set. In the Atmel AT90S1200, two I/O ports are provided (Port B and Port
25 D) having 8 and 7-bit widths. As noted in step 102 and illustrated in Figure 3, bits 3-5 of Port D are set to receive the SCAN lines of the LED display 23 and bits 1-7 of Port B are set to receive the segment lines of the LED display 23. Bit 0 of Port B and bit 6 of Port D are set to output serial data to connector J2. Steps 100 and 102 are typically executed at power-up or during a reset operation.

At step 104 it is determined if scan line 1 (PD3) is active. If not the process loops back to step 104 to later determine if scan line 1 is active. If scan line 1 is active, then at step 106, the data segment for character 1 (i.e., the first LED display 23a) is captured and stored in memory in the microcontroller U6.

5 At step 108 it is determined if scan line 2 (PD4) is active. If not the process loops back to step 108 to later determine if scan line 2 is active. If scan line 2 is active, then at step 110, the data segment for character 2 (i.e., the second LED display 23b) is captured and stored in memory in the microcontroller U6.

 At step 112 it is determined if scan line 3 (PD5) is active. If not the process
10 loops back to step 112 to later determine if scan line 3 is active. If scan line 3 is active, then at step 114, the data segment for character 3 (i.e., the third LED display 23c) is captured and stored in memory in the microcontroller U6.

 At step 116 the channel information captured at steps 106, 110 and 114 is converted into ASCII and serially transmitted to the collection meter 18 at a predetermined
15 data rate. After the transmission is complete at step 118, the process returns to step 104.

 As described above, the present invention provides for a novel apparatus and method for capturing information related to the channel to which a set-top converter box is tuned and for converting the information into data having a format compatible with a viewership data collection meter.

20 It is noted that the foregoing examples have been provided merely for the purpose of explanation and are in no way to be construed as limiting of the present invention. While the invention has been described with reference to preferred embodiments, it is understood that the words which have been used herein are words of description and illustration, rather than words of limitations. Further, although the invention has been
25 described herein with reference to particular means, materials and embodiments, the invention is not intended to be limited to the particulars disclosed herein; rather, the invention extends to all functionally equivalent structures, methods and uses, such as are within the scope of the appended claims. Those skilled in the art, having the benefit of the teachings of this specification, may effect numerous modifications thereto and changes may be made without
30 departing from the scope and spirit of the invention in its aspects.

For example, the set-top converter box 16 may be modified to include the components of the collection meter 18, such that a single set-top device performs the functions of both devices.

Patent : 6,600,000

WHAT IS CLAIMED IS:

1. A display interface device for use in determining a currently tuned-to channel of a set-top converter box having an electronic display, said electronic display indicating said currently tuned-to channel in response to drive signals provided thereto by said set-top converter device, said display interface device comprising:

an electrical connection to said electronic display, said electrical connection being adapted to communicate said drive signals;

a controller, said controller being connected to said electronic display by said electrical connection and receiving said drive signals transmitted to said electronic display,

wherein said controller receives and interprets said drive signals to generate information representative of said currently tuned-to tuned channel.

2. The display interface as recited in claim 1, wherein said electronic display comprises at least one seven-segment display element, and wherein said seven-segment display element is adapted to display an alphanumeric character representation of said currently tuned-to channel of said set-top converter box.

3. The display as recited in claim 2, wherein said drive signals are provided to plural seven-segment display elements in said electronic display using a multiplexing scheme in order to display each alphanumeric character of said currently tuned-to channel, and wherein said drive signals are input to said controller and sampled to determine said currently tuned-to channel.

4. The display interface as recited in claim 3, wherein said drive signals comprise scan signals provided over scan lines that selectively enable one seven-segment display element in said electronic display and segment signals provided over segment lines that drive each segment of said seven-segment display element, said wherein said scan lines and said segments lines are input to predetermined pins of an input/output port of said controller in order to determine said currently tuned-to channel.

5. The display interface as recited in claim 4, wherein said information representative of said tuned channel comprises an ASCII value representative of said currently tuned-to channel, and wherein said controller outputs said ASCII value to a viewership meter connected to said display interface via a second electrical connection.

5 6. The display interface as recited in claim 5, wherein said viewership meter comprises an audio matching circuit, said audio matching circuit comparing a first audio signal of a predetermined channel tuned by said viewership collection meter with a second audio signal output by a television to which said set-top converter is connected, wherein if said first audio signal and said second audio signal match, said viewership
10 collection meter determines that said channel to which said set-top converter box is tuned is said predetermined channel.

7. The display interface as recited in claim 1, wherein said information representative of said tuned channel is output to a second device connected to said display interface via a second electrical connection, and wherein said second device receives and
15 further processes said information representative of said currently tuned-to channel.

8. The display interface as recited in claim 7, wherein said second device comprises a viewership collection meter, and wherein said viewership collection meter stores said information representative of said currently tuned-to channel and forwards it to a predetermined location at selected times.

20 9. The display interface as recited in claim 8, wherein said information representative of said tuned channel comprises an ASCII value representative of said currently tuned-to channel, and wherein said controller outputs said ASCII value to said viewership meter via said second electrical connection.

10. The display interface as recited in claim 7, wherein said display interface board is adapted to receive power and additional data via said second electrical connection.

11. A system for determining viewership of channels tunable by a set-top converter box having an electronic display, said system comprising:
a display interface device connected to said electronic display; and
a viewership collection meter connected to said display interface, said viewership meter periodically storing a channel to which said set-top converter is tuned, wherein said channel to which said set-top converter is tuned is determined by said display interface and communicated to said viewership collection meter, and wherein said viewership collection meter stores said channel and forwards it to a predetermined location at selected times.

12. The system for determining viewership of channels tunable by a set-top converter box as recited in claim 11, wherein said viewership collection meter further comprises an audio matching circuit, said audio matching circuit comparing a first audio signal of a predetermined channel tuned by said viewership collection meter with a second audio signal output by a television to which said set-top converter is connected, wherein if said first audio signal and said second audio signal match, said viewership collection meter determines that said channel to which said set-top converter box is tuned is said predetermined channel.

13. The display interface as recited in claim 11, wherein said electronic display comprises at least one seven-segment display element, and wherein said seven-segment display element is adapted to display an alphanumeric character representation of said currently tuned-to channel of said set-top converter box.

14. The display as recited in claim 13, said display interface comprising a controller, wherein said drive signals are provided to plural seven-segment display elements

in said electronic display using a multiplexing scheme in order to display each alphanumeric character of said currently tuned-to channel, and wherein said drive signals are input to said controller and sampled to determine said currently tuned-to channel.

15. The display interface as recited in claim 14, wherein said drive signals
5 comprise scan signals provided over scan lines that selectively enable one seven-segment display element in said electronic display and segment signals provided over segment lines that drive each segment of said seven-segment display element, said wherein said scan lines and said segments lines are input to predetermined pins of an input/output port of said controller in order to determine said currently tuned-to channel.

10 16. A method of determining a channel to which a set-top converter box is tuned using a display interface, said set-top converter comprising an electronic display that is driven by drive signals, said method comprising:

receiving drive signals at said display interface;
determining a channel to which said set-top converter box is tuned by
15 sampling said drive signals;
generating a coded representation of said determined channel; and
outputting said coded representation.

17. The method as recited in claim 16, wherein said electronic display
comprises at least one seven-segment display element, and said drive signals comprise scan
20 signals provided over scan lines that enable each seven-segment display element and segment signals provided over segment lines that drive each segment of said seven-segment display element, said step of determining a channel to which said set-top converter box is tuned further comprising:

(a) determining if a scan line for said seven-segment display element
25 is active;

(b) if said scan line is active at step (a), then determining which of said segment lines are active to determine character being displayed by said seven-segment display element; and

(c) repeating steps (a) and (b) for each seven-segment display element
5 in said electronic display.

18. The method as recited in claim 16, wherein said step of generating a coded representation of said determined channel comprises generating an ASCII value of said channel to which said set-top converter box is tuned.

19. The method as recited in claim 18, wherein said step of outputting said
10 coded representation comprises serially transmitting said ASCII value to a viewership meter.

20. The method as recited in claim 19, further comprising:
storing, at said viewership meter, said ASCII value; and
forwarding said ASCII value at predetermined times to a central
collection site.

Patent Application No. 10/000,000

ABSTRACT

A display interface device and method for determining a currently tuned-to channel of a set-top converter box having an electronic display that indicates the currently tuned-to channel via seven-segment display elements in response to drive signals provided thereto by the set-top converter device. The display interface device includes an electrical connection to the electronic display and a controller. The controller receives the drive signals over the electrical connection and generates information representative of the currently tuned-to tuned channel for use by downstream components. The information representative of the tuned channel may be output as an ASCII value representative of the currently tuned-to channel. The display interface may be part of a viewership metering system when used in conjunction with a viewership collection meter to determine viewer habits.

2025 RELEASE UNDER E.O. 14176

FIG. 1





FIG. 2





[illegible]

FIG. 5



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Application of:

Lester L. Jarrell

Group Art Unit: not yet
assigned

For: TELEVISION AUDIENCE
MONITORING SYSTEM AND
METHOD EMPLOYING DISPLAY
OF CABLE CONVERTER BOX

Examiner: not yet assigned

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; and

I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a

☒ Utility Patent ☐ Design Patent

is sought on the invention, whose title appears above, the specification of which:

- ☒ is attached hereto.
☐ was filed on _____ as Serial No. _____.
☐ said application having been amended on _____.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to be material to the patentability of this application in accordance with 37 CFR § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119(a-d) of any **foreign**

application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of any application on which priority is claimed:

Priority Claimed (If X'd)	Country	Serial Number	Date Filed
<input type="checkbox"/>	_____	_____	_____
<input type="checkbox"/>	_____	_____	_____
<input type="checkbox"/>	_____	_____	_____
<input type="checkbox"/>	_____	_____	_____

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to be material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

Serial Number	Date Filed	Patented/Pending/Abandoned
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below:

Serial Number	Date Filed
_____	_____


I hereby appoint the following persons of the firm of **WOODCOCK WASHBURN KURTZ MACKIEWICZ & NORRIS LLP**, One Liberty Place - 46th Floor, Philadelphia, Pennsylvania 19103 as attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

<u>Lawrence A. Aaronson</u>	Reg. No. <u>38,369</u>
<u>Michael D. Stein</u>	Reg. No. <u>34,734</u>
<u>Dale M. Heist</u>	Reg. No. <u>28,425</u>

Address all telephone calls and correspondence to:

Lawrence A. Aaronson
**WOODCOCK WASHBURN KURTZ
MACKIEWICZ & NORRIS LLP**
One Liberty Place - 46th Floor
Philadelphia PA 19103
Telephone No.: (215) 568-3100
Facsimile No.: (215) 568-3439

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name: Lester L. Jarrell	 Signature Date of Signature: <u>9/30/98</u> Citizenship: <u>U.S.</u>
Mailing Address: 12226 Lakeside Avenue Lakeside, CA 92040	
City/State of Actual Residence: Lakeside, California	

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Application of:

LESTER L. JARRELL

Serial No.: HERewith

Group Art Unit: Unknown

Filed: HERewith

Examiner: Not yet assigned

For: TELEVISION AUDIENCE
MONITORING SYSTEM AND
METHOD EMPLOYING DISPLAY OF
CABLE CONVERTER BOX

Assistant Commissioner for Patents
Washington DC 20231

Sir:

ASSOCIATE POWER OF ATTORNEY


The undersigned, of the firm WOODCOCK WASHBURN KURTZ
MACKIEWICZ & NORRIS LLP, One Liberty Place - 46th Floor, Philadelphia,
Pennsylvania 19103, Attorney and/or Agents for Applicant(s), hereby appoints the following:

Robert B. Washburn	Registration No. 16,574	Michael D. Stein	Registration No. 34,734
Richard E. Kurtz	Registration No. 19,263	Albert J. Marcellino	Registration No. 34,664
John J. Mackiewicz	Registration No. 19,709	David R. Bailey	Registration No. 35,057
Norman L. Norris	Registration No. 24,196	Barbara L. Mullin	Registration No. 38,250
Albert W. Preston, Jr.	Registration No. 25,366	Lynn A. Malinoski	Registration No. 38,788
Dale M. Heist	Registration No. 28,425	Lori Y. Beardell	Registration No. 34,293
Philip S. Johnson	Registration No. 27,200	Doreen Yatko Trujillo	Registration No. 35,719
John W. Caldwell	Registration No. 28,937	Michael P. Straher	Registration No. 38,325
Gary H. Levin	Registration No. 28,734	Paul K. Legaard	Registration No. 38,534
Steven J. Rocci	Registration No. 30,489	Kevin M. Flannery	Registration No. 35,871
Dianne B. Elderkin	Registration No. 28,598	David A. Cherry	Registration No. 35,099
Francis A. Paintin	Registration No. 19,386	Anthony J. Rossi	Registration No. 24,053
John P. Donohue, Jr.	Registration No. 29,916	Michael J. Swope	Registration No. 38,041
Henrik D. Parker	Registration No. 31,863	Michael J. Bonella	Registration No. 41,628
Suzanne E. Miller	Registration No. 32,279	Harold H. Fullmer	Registration No. 42,560
Lynn B. Morreale	Registration No. 32,842	John E. McGlynn	Registration No. 42,863
Mark DeLuca	Registration No. 33,229	Kimberly R. Hild	Registration No. 39,224
Joseph Lucci	Registration No. 33,307	Jonathan M. Waldman	Registration No. 40,861
Michael P. Dunnam	Registration No. 32,611	Joseph R. Condo	Registration No. 42,431

Michael K. Jones	Registration No. 41,100
Frank T. Carroll	Registration No. 42,392
Steven H. Meyer	Registration No. 37,189
John M. Paolino	Registration No. 40,340
Rena Patel	Registration No. 41,412

his/her associates with full power to prosecute the above-identified application and to transact all business in the Patent Office connected therewith and requests that correspondence continue to be directed to the firm of WOODCOCK WASHBURN KURTZ MACKIEWICZ & NORRIS LLP at the above address.

Date: October 9, 1998


Lawrence A. Aaronson
Registration No. 38,369

Woodcock Washburn Kurtz
Mackiewicz & Norris LLP
One Liberty Place - 46th Floor
Philadelphia PA 19103
Telephone: (215) 568-3100
Facsimile: (215) 568-3439

© 1997 WWKMN